

Fasson® 2 Mil Clear BOPP TC/R3500/40#SCK**Spec# 78148****Facestock:**

Fasson® 2 Mil Clear BOPP TC is a topcoated biaxially oriented, co-extruded polypropylene film with excellent clarity. The surface has been modified for improved ink adhesion. This product has excellent moisture resistance and good diecutting and dispensing characteristics. Printable by many web screen, UV letterpress, flexographic solvent and water-based inks. Not recommended for thermal transfer printing. Use caution when applying inks out to the edge of the label, particularly UV screen inks and UV cured varnishes. High shrinkage coatings can cause labels to lift off the liner or substrate. In-house testing is always recommended prior to final ink selection.

Basis Weight:	n/a
Caliper:	0.0020 inches ± 10%
Tensile:	MD 20,580 psi CD 39,750 psi
Tear:	n/a
Stiffness:	n/a

Adhesive:

Fasson® R3500 is a specially formulated acrylic adhesive designed for ease of removability while maintaining good peel performance.

Type:	Emulsion Acrylic
Minimum Application Temperature:	+40° F
Service Temperature Range:	0° F to +200° F

Typical Performance Data: Tested with 2 Mil Clear BOPP**Stainless Steel**

Loop Tack:

Peel Adhesion: 0.87 Lbs

PET Flow Wrap

Loop Tack:

Peel Adhesion: 0.90 Lbs

Liner:

40#SCK is a bleached super-calendered kraft stock featuring high internal strength, toughness and tear resistance. Used primarily for roll-to-roll label applications.

Basis Weight:	42# per ream $\pm 10\%$ (500 sheets 24" X 36")
Caliper:	0.0025 inches $\pm 10\%$
Tensile:	MD 38# per inch width CD 20# per inch width
Tear:	MD 36 grams CD 41 grams

Total Construction Caliper (approximate): 0.0053 inches $\pm 10\%$

Shelf Life

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH

Statement of Practical Use

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined suitability of such products for its purposes. AVERY DENNISON products are warranted to the original purchaser to be free from defects in material or workmanship for a period of one year from date of shipment. Purchaser's sole and exclusive remedy for breach of this warranty shall be the replacement of the defective products or, at AVERY DENNISON's option, the issuance of a credit or refund in an amount up to the purchase price of the defective product. In no event shall AVERY DENNISON be responsible for claims beyond the purchase price of the defective product.

THE WARRANTY SPECIFICALLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OR MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. IN NO EVENT SHALL AVERY DENNISON BE LIABLE TO PURCHASER OR ANY OTHER PARTY FOR INDIRECT, CONSEQUENTIAL, INCIDENTAL, SPECIAL OR PUNITIVE DAMAGES.

No representative or agent of AVERY DENNISON is authorized to give any guarantee or warranty or make any representation contrary to the above. No waiver, alteration, addition or modification of the foregoing conditions shall be valid unless made in writing and signed by an executive officer of AVERY DENNISON.



Fasson Roll North America
Phone: 800-944-8511
www.fasson.com

FASSON
Ideas that work for you™